© All right reserved. Midj S.p.a. - VAT nr IT01102740931

Zelig DP

design Paolo Vernier, 2009

Task chair with four ways base in chrome. Shell available in eight colours of policarbonate, wood finish dark oak or natural oak or upholstered in leather, ecoleather, fabric or custom's fabric.



Finishing and Materials

Structure



Chrome

Coating



Policarbonate



Pix Fabric
13 colors



Mirage Fabric
16 colors



Natural Wool Fabric
15 colors



Long Life Fabric
13 colors



Bubble fabric
14 colors



Hot Fabric
13 colors

Inca Ecoleather
17 colors



Magic Ecoleather
17 colors



Vintage Ecoleather
4 colors




Fiore Leather
15 colors

Special Leather
8 colors



Vintage Leather
4 colors

Dimensions



Dimension	cm	inch
A	91/90	31.9/35.4

Dimension	cm	inch
B	51	20.1
C	62	24.4
D	46/55	18.1/21.2

Volumetric Details

Weight 9
Volume 0.31 mc
Package 2

Downloads

Zelig Brochure (pdf) - http://www.midj.com/images/uploads/resources/zelig.pdf

Materials Certifications

Mirage Fabric
Mantindale: 100.000 cycles Composition: 100% Polyester Shrinking about 1% Fire retardant fabric: classe 1IM, B1 DIN 4102, M1, B1 OENORM Part.1, BS 5852 Crib 5, EN 1021, USA Calif. Bull 117, IMO 688 (17) - IMO 563 (14) - IMO 653 (16)

Natural Wool Fabric
Martindale: 100.000 cycles Composition: 70% Wool, 25% Polyamid, 5% Fibers Shrinking about: 1% Fire retardant fabric: BS 5852 part. 1, Cigaret test, Match test

Long Life Fabric
Martindale 40.000 cycles Composition: 74% Polyester, 18% Cotton, 8% Acrylic Shrinking about 1%

Bubble fabric
Martindale: 35.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

Hot Fabric
Martindale: 45.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

Inca Ecoleather
Martindale: 50.000 cycles Composition: 6% Cotton, 6% Polyester, 88% PVC Shrinking about: 1% Fire retardant fabric: Classe 1IM, BS 5852 Part. 1, IMO RES. A.652(16)

Magic Ecoleather
Martindale: 150.000 cycles Composition: 31% Cotton, 48% Polyurethane, 21% Polyester Shrinking about: 1% Fire retardant ecoleather: Classe 1IM, BS 5852 Part. 1, Cigaret Test, Match Test

Vintage Ecoleather
Ecoleather phtalatic free - R.E.A.C.H. 1907/2006/EU Breathable ecoleather Composition: 90% PVC, 7% Polyurethane, 3% Cotton Shrinking about 1%

Fiore Leather
BS 5852 parte 1; ISO 5402>50000 cicli; ISO 105B02 ? 5; ISO 3377-1 ?20 N; ISO 11644 ? 2.5 N/Cm; EN 1021/1-2; EN ISO 17233 -20°; IMO RES A 6528(16)

Vintage Leather
UNI EN ISO 105 B02 ?3; ISO 5402>50000 cicli; ISO 3377-1?20; UNI EN ISO 11640 Secco - Dry 50 c ?4 Umido - Wet 20 c ? 3; Sudore - Sweat 20 c ? 3