




Downlights | topLED 70 W 24 V | CRI 80
65436N00



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	70 W
Luminous flux (source)	9823 lm
Tensione	24V
CCT / Tonalità	4000 K
Colour rendering index	80 Ra
C.C. / C.V.	CV
Safety class	3
IP	IP40
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-20°C / +50°C
Driver included	No
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	7.4 Kg

Finishing casing	
Material	Aluminium
Colour	bronze
Processing	Coating

Electronics



99074
DALI 1-10V Multi Channel 3ch. 24V DC 216 W



99374
On/Off Driver 198-264V AC / 185-275V DC 75 W



99077
N/O button Multi Channel 3ch. 24V DC 216 W

Downlights | topLED 70 W 24 V | CRI 80
65436N00

Single emission downlights for indoor application. The natural white LED light source with a general lighting light distribution is composed of 336 topped LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 9823 lm, with a 140.3 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a bronze finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 7.4 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 70 W.

The device features protection class III and can be ceiling-mounted, with a 1431 mm diameter hole (in plasterboard).

Illuminotechnical Features	
Luminous flux (source)	9823 lm
Colour temperature	4000 K
Standard Deviation of Colour Matching	2 Step MacAdam
Colour rendering index	80 Ra