
Lona C 600

SOP 3600 lm 42 W 830 DALI IP20 white


ARTICLE NO: 18272113101



White structure




Dimension



Dimension (mm): **D:** 610 **H:** 120

Photometry



Product description

Installation Ceiling mounted (C) **Optic** Satin opal PMMA diffuser **Nominal Luminaire Luminous flux** 3600 lm **Light source luminous flux** 5408 lm **Power** 41.6 W **Correlated colour temperature - CCT** 3000 K **Colour Rendering Index - CRI** 80 **Chromaticity tolerance (initial MacAdam)** 3 **Lumen maintenance factor** 50000h L80 B10 at 35°C **Driver** DALI dimmable LED driver **Power supply** 230V 50Hz **IP Protection** IP20 **Weight** 8,50 kg **EAN number** 3831116791288 **Energy class** A++

Light output ratio	
LOR	66,6
ULOR	0
DLOR	66,6
Total luminous flux	3602
Luminaire efficacy (LEF)	87
UGR values	
X=4H, Y=8H	S = 0,25H
Radiant class	70/50/20
Transverse	21.8
Longitudinal	21.8
Classification	
BZ	BZ 4 / 1.5 / BZ 5
UTE	0.67 E
DIN	A30
CIE	48 78 95 100 67