
Demi RV air

HMP 2400 lm 20 W 830 DALI 100x1720mm IP20 white


ARTICLE NO: 11102166511



White




Dimension



Dimension (mm): **L:** 1720 **W:** 100 **H:** 85

Cut Out (mm): **Hco:** 100

Photometry



Light output ratio	
LOR	71,8
ULOR	0
DLOR	71,8
Total luminous flux	2377
Luminaire efficacy (LEF)	106
UGR values	
X=4H, Y=8H	S = 0,25H
Radiant class	70/50/20
Transverse	12.2
Longitudinal	15.4
Classification	
BZ	BZ 1
UTE	0.72 B
DIN	A60
CIE	81 99 100 100 72

Product description

Installation Recessed ceiling (RV) **Optic** Satin silver-coated aluminium double parabolic louvre **Material** Steel-sheet, powder coated

Nominal Luminaire Luminous flux 2400 lm **Light source luminous flux** 3310 lm **Power** 22.4 W **Correlated colour temperature - CCT** 3000 K

Colour Rendering Index - CRI 80 **Chromaticity tolerance (initial MacAdam)** 3 **Lumen maintenance factor** 50000h L80 B10 at 35°C **Driver** DALI dimmable LED driver **Sensor** No Sensor **Power supply** 230V 50Hz **IP Protection** IP20

IK Protection IK05 **Weight** 4,20 kg **Weight of luminaire with packaging.** 4,80 kg

Energy class A++