REO S OK S1 / REO 2S OK S1

Correcte verwijdering van dit product (Elektrische & elektronische afvalapparatuur)
Comment éliminer ce produit (Déchets d'équipements électriques et électroniques)
Korrekte Entsorgung dieses Produkts (Elektromüll)
Correct disposal of this product (Waste electrical & electronical equipment)
Eliminacion correcta de este producto (Material eléctrico y electronico de descarte)
Corretto smaltimento del prodotto (Rifiuti elettrici ed elettronici)

Enkel geschikt voor toestellen op zeer lage spanning (minder dan 50 V AC)
Convient uniquement pour les produits à très basse tension (moins de 50 V AC)
Geeignet für Güter mit sehr niedriger Spannung (unter 50 V AC)
Only suited for goods at very low voltage (below 50 V AC)
Se recomieda únicamente para aquellos productos de tensión muy baja (menos de 50 V AC)
Vale unicamente per i prodotti a tensione molto bassa (inferiore a 50 V AC)


Toestel niet geschikt om te worden afgedekt met thermische isolatie.
Luminaire not suitable for covering with insulating material.
Luminaires non appropriées pour recouvrement d'un matériau isolant thermique.
Das Gerät/Die Leuchte darf nicht abgedeckt werden mit thermischer Isolation.
Luminaria no apta para cubrir con material aislante.
Apparecchio non adatto per essere coperto da materiale isolante.

Installeer het armatuur enkel in ruimten waar direct contact met water onmogelijk is.
Cet équipement doit être installé dans des pièces hors de toute projection d'eau.
Diese Leuchte darf nur in Räumen verwendet werden, in denen ein direkter kontakt mit wasser nicht möglich ist
This fitting should only be installed in rooms where direct contact with water is impossible
Este aparato solamente puede ser instalado en habitaciones donde el contacto directo con el agua sea imposible
Questo apparecchio di illuminazione deve essere installato solamente in locali in cui il contatto con l'acqua è impossibile.

Gelijkstroomtoevoer
Alimentation DC
GS-Zufuhr
DC supply
Alimentación de CC
Alimentazione CC

Bevestiging plafond inbouw
Montage plafond encastré
Montage decke eingebaut
Fixation ceiling recessed
Montaje techo empotrado
Montaggio soffitto incasso


DO NOT TOUCH OR CLEAN THE LED ARRAY!




- Use only power supplies that are certified according to the applicable IEC or UL safety standards.
- Use only SELV power supplies.
- Check the ratings of the power supply with those of the luminaire.
  The maximum current rating must be taken into account.
  The indicated typical voltage must not be used to select a constant voltage power supply but is indented to used to select a constant current power supply that is able to cover that typical voltage.
- Take appropriate ESD measures. Avoid touching bare conductors.
- Leds or led luminaires that require a current controlled power supply must never be connected in parallel.
- Leds can be damaged by the contact with certain chemicals or chemical gasses.
  Therefore led domes or led engines should never be cleaned with chemical substances.
  The following substances have proven to have a negative influence on the performance and must not be used in the direct environment of a led luminaire.
  - Methyl acetate or ethyl acetate (i.e., nail polish remover)
  - Cyanoacrylates (i.e., "Superglue")
  - Glycol ethers (including Radio Shack® Precision Electronics Cleaner - dipropylene glycol monomethyl ether)
  - Formaldehyde or butadiene (including Ashland PLIOBOND® adhesive)
  - Dymax 984-LVUF conformal coating
  - Loctite Sumo Glue
  - Gorilla Glue
  - Bleach, Bleach-containing cleaners, sprays
  - Loctite 384 adhesive
  - Loctite 7387 activator
  - Loctite 242 threadlocker
- Remove insulation and/or provide sufficient ventilation so that the indicated max Tc is not surpassed.
- Leds are susceptible to switching transients. Therefore switching must be done in the primary circuit of the power supply.
- DELTA LIGHT recommands to use the power supplies that are indicated in the Lighting Bible.
- Respect polarity
- Don't test LED luminaires one by one on a powersupply that is switched on.

Reo s ok S1
Reo 2s ok S1

Manual /






4000K		
REFLECTOR FL-33°	REO S OK 4033 S1◇ 202 38 8124 ◇ ◇ = A / W	REO 2 S OK 4033 S1◇ 202 38 8224◇ ◇ = A / W
REFLECTOR WFL-50°	REO S OK 4050 S1◇ 202 38 8134 ◇ ◇ = A / W	REO 2 S OK 4050 S1◇ 202 38 8234◇ ◇ = A / W
3000K		
REFLECTOR FL-33°	REO S OK 3033 S1◇ 202 38 8122 ◇ ◇ = A / W	REO 2 S OK 3033 S1◇ 202 38 8222◇ ◇ = A / W
REFLECTOR WFL-50°	REO S OK 3050 S1◇ 202 38 8132 ◇ ◇ = A / W	REO 2 S OK 3050 S1◇ 202 38 8232◇ ◇ = A / W
2700K		
REFLECTOR FL-33°	REO S OK 2733 S1◇ 202 38 8123 ◇ ◇ = A / W	REO 2 S OK 2733 S1◇ 202 38 8223◇ ◇ = A / W
REFLECTOR WFL-50°	REO S OK 2750 S1◇ 202 38 8133◇ ◇ = A / W	REO 2 S OK 2750 S1◇ 202 38 8233◇ ◇ = A / W

98 x 80 max.30

ADJUSTABLE 0°- 30° / 350°
INCL.1 x POWERLED WHITE 6-8W
INCL.1 x REFLECTOR
EXCL.LED POWER SUPPLY 500-700mA-DC
CURRENT CONTROLLED

CE 0,4 IP20

OPTIONS
PLASTERKIT 170
LED POWER SUPPLY 500 / 700mA-DC
LED POWER SUPPLY MULTI-POWER DIM



190 x 98 x 80 max.30

ADJUSTABLE 0°- 30° / 350°
INCL.2 x POWERLED WHITE 6-8W
INCL.2 x REFLECTOR
EXCL.LED POWER SUPPLY 500-700mA-DC
CURRENT CONTROLLED

CE 0,8 IP20

OPTIONS
LED POWER SUPPLY 500 / 700mA-DC
LED POWER SUPPLY MULTI-POWER DIM


CE L.LI.B A4
A
DEEL
PARTIE
TEIL
PART
PARTE
PARTE

DELTALIGHT®

Delta Light nv Muizelstraat 2 B-8560 Wevelgem (Moorsele) Belgium T+32 (0)56 435 735 F+32 (0)56 435 736 info@deltalight.com **www.deltalight.com**


REO S OK S1


DELTALIGHT





Tc = max 70°C @ 700 mA
80°C @ 500 mA


Accessory Set














ELECTRICAL CONNECTION









REO 2 S OK S1


DELTALIGHT





Tc = max 70°C @ 700 mA
80°C @ 500 mA


Accessory Set











ELECTRICAL CONNECTION

